


PARTS LIST		
DESCRIPTION	PART NUMBER	QTY
CONTROL PANEL	DUO2.CAN	1
SENSOR OPTION LEFT	SENSOR OPTIONS	1
SENSOR OPTION RIGHT	SENSOR OPTIONS	1
JOYSTICK (OPTIONAL)	JOYSTICK OPTIONS	1
HYDRAULIC CORD	A.RS.080	1
CAN CORD	A.RS.107	1
CAN CORD	A.RS.110	2
CAN CORD	A.RS.111	1
HYDRAULIC CORD	A.RS.127	1
POWER CORD	A.RS.001.NC	1
HYDRAULIC BREAKAWAY BOX	IB.DUO2.HYD	1
DUO2 INTERFACE BOX	IB.DUO2.CAN	1
HIRSCHMANN OR DEUTSCH CONNECTORS (OPTIONAL)	P.CONN.059/043/061	Up to 8

LASER RECEIVER OPTIONS	
R.ULS.CAN	5 CHANNEL RECEIVER
R.ULS.MM.CAN	5 CHANNEL MILLIMETER RECEIVER

CAN CORD OPTIONS	
A.RS.135	1.0m
A.RS.111	2.5m
A.RS.110	5.0m
A.RS.107	10.0m
A.RS.106	Curly Cord, 1.7m un-strechd; 8.5m stretched

OPTIONAL 8P-8S ADAPTOR FOR EXTENDING CAN CORDS (P/N: P.CONN.018)	
	

JOYSTICK OPTIONS	
A.RS.082	PROPORTIONAL JOYSTICK, AVAILABLE IN MACHINE-SPECIFIC VARIANTS
A.RS.076	MULTI-STICK FOR DUO2
A.RS.131	JOYSTICK CORD FOR SKID STEER, BARE WIRE

RevNo	Revision note	Date	Signature	Checked	Tolerances	Path: \1-ADM\Product Documents\Setup Diagrams\Receiving Systems\			
1	Rearranged to be consistent with the rest of the setup diagrams.	08/02/21	N.A.	D.R. & C.R.	Unless Stated:	Material:		Finish:	
2	Updated the template.				xx.x = +/- 0.1	Drawn by:	N.A.	Checked by:	D.R. & C.R.
3	Updated graphics and cable, sensor & joystick options	4/08/25	T.K.	D.R.	xx.xx = +/- 0.05	Unit:		Date:	4/08/25
					xx.xxx = +/- 0.02			Title: SETUP DIAGRAM FOR DUO2 WITH HYDRAULIC BREAKAWAY JUNCTION BOX	
								Drawing No:	Version: 3
						MOBA Mobile Automation Australia 90 Willandra Drive, Epping Victoria 3076, Australia https://moba.com.au		Sheet:	1/1

